



GC 135



GX 25



GXH 50



GX 100 TAMP



GX 390



iGX 270



iGX 440



GX 690



GXV 160



GCV 160











GCV 530



GXV 630

www.honda-engines-eu.com

HONDA
ENGINES

	 n/min														
model	min.	max.	IN mm	EX mm	I	mm	PART NUMBER		mm	Nm	Nm	Nm			
G 100K1	1400 ± 150	4200	0,12 ± 0,04	0,12 ± 0,04	0,45	0,6-0,7	98073-54744	BMR 4A	0,4 ± 0,2	10	5	50			
G 100K2		3850 ± 150		0,20 ± 0,04	0,7		98073-54776	BPMR 4A		25	12	65 ± 5			
G 150							98076-54716	BR 4HS							
G 150K1							98076-54919	BP 4HS-10 (CDI)					0,3 ± 0,1		
G 200							98076-54770	B 4H					0,4 ± 0,2		
G 200K1							98076-54716	BR 4HS					—		
GC 135 / 160 GC 190	1400 ± 150	3850 ± 150	0,15 ± 0,04	0,20 ± 0,04	0,6	0,7-0,8	98079-56846	BPR 6ES	0,4 ± 0,2	—	12	52			
GS 160 / 190	1400 ± 150	3850 ± 150	0,15 ± 0,04	0,20 ± 0,04	0,6	0,7-0,8	98079-56846	BPR 6ES	0,4 ± 0,2	—	12	52			
GX 22 / 31	3100 ± 200	10000	0,12 ± 0,02	0,15 ± 0,02	0,1	0,6-0,7	98056-55777	CR5 HSB	0,35 - 0,50	—	6	15			
GX 25 / 35			0,08 ± 0,02	0,11 ± 0,02	0,08		31915-Z0H-003	CMR5H	0,30 - 0,50			14,7			
GXH 50	2500 ± 200	7800 ± 150	0,08 ± 0,02	0,11 ± 0,02	0,25	0,6-0,7	98056-55777	CR5 HSB	0,4 ± 0,1	—	5	21,5			
GX 100 STD	1550 ± 150	3850 ± 150	0,15 ± 0,02	0,20 ± 0,02	0,4	0,6-0,7	98056-55777	CR5 HSB	0,35 ± 0,15	—	5	42			
GX 100 TAMP		4000 ± 200													
GX 120	1400 ± 150	3850 ± 150	0,15 ± 0,02	0,20 ± 0,02	0,6	0,7-0,8	98079-56846	BPR 6ES	0,4 ± 0,2	24	12	75			
GX 160			0,15 ± 0,02	0,20 ± 0,02											
GX 160 T2			0,08 ± 0,02	0,10 ± 0,02											
GX 200			0,15 ± 0,02	0,20 ± 0,02											
GX 240	1400 ± 150	3850 ± 150	0,15 ± 0,02	0,20 ± 0,02	1,1	0,7-0,8	98079-56846	BPR 6ES	0,4 ± 0,2	35	14	128			
GX 270															
GX 340															
GX 390															
GX 360	1400 ± 150	3850 ± 150	0,12 ± 0,02	0,12 ± 0,02	1,1 / 1,4*	0,6-0,7	98076-54747	BPR 4HS	0,4 ± 0,2	22,5	22	115			
GX 640	1400 ± 100	3750 ± 100		0,20 ± 0,02	2,0 / 2,3*	1,0-1,1	98079-55145	BPR 5ES-11	—	55	29	71			
GX 610 / 620	1400 ± 150	3850 ± 150	0,15 ± 0,02	0,20 ± 0,02	1,2 / 1,5*	0,7-0,8	98079-56846	BPR 6ES	0,4 ± 0,2	30	17	200			
GX 610K1 / 620K1					1,5 / 1,8*										
GX 670					1,6 / 1,9*										
GX 630 / 660 / 690					0,08 ± 0,02		0,10 ± 0,02	1,5 / 1,7*		98079-5587G	ZFR 5F	—	22	235	
GV 100K1	2000 ± 150	2950 ± 50	0,12 ± 0,04	0,12 ± 0,04	0,4	0,6-0,7	98073-54744	BMR 4A	0,4 ± 0,2	10	5	50			
GV 100K2							98073-54776	BPMR 4A							
GCV 135 / 160 / 190	1700 ± 150	2950 ± 50	0,15 ± 0,04	0,20 ± 0,04	0,55	0,7-0,8	98079-56846	BPR 6ES	0,4 ± 0,2	—	12	52			
GCV 520 / 530	1425 ± 175	3400 ± 150	0,10 ± 0,04	0,15 ± 0,04	0,9 / 1,05*	0,7-0,8	98079-56846	BPR 5ES	0,4 ± 0,2	32	12	157			
GSV 160 / 190	1700 ± 150	2950 ± 50	0,15 ± 0,04	0,20 ± 0,04	0,55	0,7-0,8	98079-56846	BPR 6ES	0,4 ± 0,2	—	12	52			
GXV 50	2500 ± 200	4900 ± 100	0,08 ± 0,02	0,11 ± 0,02	0,25	0,6-0,7	98056-55777	CR5 HSB	0,4 ± 0,1	—	6	21,5			
GXV 120	2000 ± 150	3100 ± 150	0,10 ± 0,03	0,15 ± 0,03	0,6	0,6-0,7	98079-55846	BPR 5ES	0,4 ± 0,2	24	12	75			
GXV 140	2100 ± 150	3100 ± 100	0,15 ± 0,02	0,20 ± 0,02		0,7-0,8	98079-55846		0,35 ± 0,15		52				
GXV 160	1700 ± 150	3200 ± 150					0,65		98079-55846		0,4 ± 0,2	75			
GXV 160K1, H2	1400 ± 150	3400 ± 150	0,15 ± 0,02	0,20 ± 0,02	1,1	0,7-0,8	98079-55846	BPR 5ES	0,4 ± 0,2	35	14	115			
GXV 270							3300 ± 150								
GXV 340K1															
GXV 340K2, T2															
GXV 390			0,10 ± 0,02	0,15 ± 0,02											
GXV 520	1425 ± 175	3400 ± 150	0,10 ± 0,04	0,15 ± 0,04	0,9 / 1,05*	0,7-0,8	98079-55846	BPR 5ES	0,4 ± 0,2	32	12	157			
GXV 530															
GXV 610 / 620	1400 ± 150	3400 ± 150	0,15 ± 0,02	0,20 ± 0,02	1,8 / 2,1*	0,7-0,8	98079-55846	BPR 5ES	0,4 ± 0,2	30	17	200			
GXV 610K1 / 620K1					1,7 / 2,2*		98079-5587V	ZGR 5A		34	12	196			
GXV 670					1,6 / 1,9*										
GXV 630 / 660 / 690					3400 ± 150		0,08 ± 0,02	0,10 ± 0,02		1,7 / 1,9*	98079-5587G	ZFR 5F	—	22	235